Installation Manual for Intelligence Line

II -MD80 CRV NEO

3 inch center speaker

Part Nr 280141

Compatible with: Honda CR-V 2023

Please read installation manual carefully before beginning installation!



Rainbow Audio GmbH - Bernbrunnerstr. 54 - 74831 Gundelsheim www.rainbow-audio.de info@rainbow-audio.de



Dear Music Lover.

We congratulate you on your purchase of our superior product and thank you for placing your trust in rainbow. With over 30 years of engineering expertise in car audio speakers and belef in Golden Spiral for product design, rainbow has created a wide range of products that reproduce life-like sound with all the details and emotions you can hope for. Rainbow guarantees outstanding quality and we wish you many pleasant hours enjoying your favorite music with our high-performance products. We have put together this installation manual with great consideration of different mechanical and acoustical features to help you better understand and operate rainbow products. And we'd love to hear your questions, feedback and improvement successors via email info@rainbow-audio.de.

Best wishes.

Your Rainbow Team

Safety Instruction

Attention

Please read all warnings found in this manual. This information is included and highlighted to inform you of the potential risks of personal injury or damage to property.

Our products are intended for those who want to upgrade their car audio systems and enjoy unbeatable sound performance in cars. The relevant safety regulations regarding related auto parts, the regulations of internal vehicle safety, as well as the regulations of the authorized vehicle manufacturers should be followed diligently.

Hearing Damage

Continuous exposure to sound pressure levels over 85 dB may cause permanent hearing loss. High-powered auto sound system could produce sound pressure levels over 130 dB, which may cause damage to hearing. Use common sense and avoid such risks,

Volume and Driver Awareness

Use of audio components can impair your ability to hear necessary traffic sounds and may constitute a safety hazard while driving your automobile.

Rainbow accepts no liability for hearing loss, bodily injury or property damage as a result of use or misuse of this product.

1

Installation Notice

Do not use your automobile until all components of the loudspeaker system have been secured to the interior framework. Failure to do so may turn a component into a dangerous, flying projectile during a sudden stoo or accident.

We recommend disconnecting the battery before beginning installation of the loudspeaker system. Please ask your car dealer if disconnecting the battery is feasible without any problems.

Always be meticulous when removing interior trim panels, Car manufacturers use a variety of fastening devices that can be damaged in the disassembly process.

If sheet metal must be cut or removed, contact your authorized car dealer for professional advice. By damage to supporting body structures the safety certificate may be withdrawn.

Shock Hazard!

Do not touch the connectors while the system is running.


Warranty

All rainbow products come with a year's warranty on all parts, starting from the date of purchase from the authorized retailer. Only the first buyer is entitled to this warranty policy, which would be invalid in case of products being transferred.

The warranty covers all material and manufacturing defects, however it does not cover mechanical defects, defects caused by electrical overload and foreign interference by unauthorized people.

This document is protected by copyright. It can not be, in whole or in part, duplicated, printed, transmitted or otherwise exploited in any manner without written permission of Rainbow Audio GmbH, Germany. Painbow reserves the right to modify or improve the desired products without prior notice. All rights reserved.

CONTENTS OF THE PACKAGE



TECHNICAL DATA

IL-MD80 CRV NEO

Frequency Response/Impedance



TECHNICAL DATA

T/S Parameters	
Cone	Fiber Glass
Sensitivity	86 dB/W/m
Nominal Power	10 W
Peak Power	20 W
Impedance	4 Ω
Re	3.4 Ω
Fs	200Hz
Frequency Response	200Hz - 10kHz
Qms	1.6
Qes	1.8
Qts	0.86
Mms	2.8 g
Cms	217 uM/N
Sd	3.2 cm ²
Vas	319 ml
BL	2.6 Tm
Magnet Dimension	Φ24.5*5mm N42
Voice Coil Diameter	25.5 mm
Voice Coil Height	5 mm
Mounting Diameter	/
Mounting Depth	1
Weight	100g

4

亲爱的音乐爱好者:

根別総购买了我们的优质产品,感谢您对影化的信任。影虹拥有超过30年的汽车音响产品开发技术和生产 经验,并遵循拥有两千多年历史的原金分割率。制造出富有音乐度,声音自然动听的音响器材。 彩虹汽车音响音质卓越,性能优良,让您尽情享受音乐之美。我们结合了不同的机械和汽车声学特点编写 了这本安装手册,帮助您更好地了解和使用彩虹产品。如您有任何疑问、反馈和改善建议,请发邮件至 info@rainbow-audiode。我们将不并感谢。

最美好的祝愿

彩虹团队

安全指南

注意

请仔细阅读用户手册中的警示,我们在此注明并强调这些信息是为提醒您免受潜在的人身伤害或设备损坏。

如您想要升级汽车音响系统、乐享旅程,彩虹产品—定是您的不二之选。汽车零部件相关安全守则,车内 安全守则和授权汽车生产商相关守则都须严格遵守。

听力损害

长时间聆听高于85分贝音量的声音可能会造成永久性听觉损失。而大功率音响系统产生的声音高于 130分贝,可能会损伤听力。请合理调节系统音量及聆听时间,避免以上风险。

音量和安全驾驶

驾驶时,使用音响系统可能会让你听不清周围的交通声,进而引发交通事故。 彩虹对因产品使用不当引起的听力损伤。身体伤害或产品性能损坏极不负责。

安装须知

扬声器系统的全部元件未在车内固定好之前,不要驾驶汽车。否则,在急刹车或汽车事故时,扬声器元件 可能成为危险的抛射物。

建议在开始安装扬声器系统之前取下汽车蓄电池。请咨询您的汽车经销商这样操作是否可行,不会引发任何问题。

拆卸内饰板时须格外小心。汽车生产商使用的多种紧固装置都可能在拆卸过程中被损坏。

5

如需切割或拆卸金属板,请联系授权汽车经销商,获取专业建议。支撑结构损坏,可能会导致安全证书被 撤回。

触电危险!

音响系统运行时,不要触摸接线端口。

质保

彩虹承诺为所有产品提供1年的法定质保期,确保所有部件在保修期内良好运行。保修期从授权经销商处 购买产品之日开始计算。只有一手客户享受质保政策,保修权不可转让。

保修对象涵盖材料及生产缺陷。而机械损坏、电压过载引起的损坏、非授权人员对产品维修或拆卸造成的 故障损坏皆不属于保修范围。

本文档受版权保护。未经彩虹公司事先书面许可,禁止以任何形式复制、打印、转发或利用部分或全部内容。彩虹公司保留修改或改进产品的权利,恕不另行通知。版权所有。

包装内容






×1

技术资料

IL-MD80 CRV NEO

频率响应/阻抗



技术资料

技术参数	
振膜	白色玻纤盆
灵敏度	86 dB/W/m
額定功率	10 W
峰值功率	20 W
标称阻抗	4Ω
直流阻抗	3.4 Ω
谐振频率	200Hz
頻率响应	200Hz = 10kHz
机械品质因数值	1.6
电品质因数值	1.8
总品质因数值	0.86
振动质量	2.8 g
力顺	217 uM/N
振动面积	3.2 cm ²
等效容积	319 ml
磁力	2.6 Tm
磁铁尺寸	Ф24.5*5mm N42
音圈直径	25.5 mm
音圏高度	5 mm
安装直径	T.
安装深度	/
重量	100g



